

PLM51 I²C software interface IIC51 (version 0.5)**ETV/AN89004***Author: R.C.J. Brink, Eindhoven***1. INTRODUCTION.****1.1. Purpose.**

This document is a user manual for the I²C software module IIC51. It is intended for Intel PLM51 users who need to control an I²C bus. This document assumes some basic knowledge about I²C and Intel PLM51.

1.2. Scope.

IIC51 is a software module to provide an Intel PLM51 user with a set of procedures to control a bi-directional I²C bus. These procedures have been coded in Intel ASM51 and have been optimized for speed. IIC51 supports all common used I²C master transmitter and master receiver protocols. Each different protocol corresponds to one of the procedures in IIC51. IIC51 is available in two different versions:

IIC51S:

IIC51S is a module for singlemaster I²C to be used on microcontrollers of the 8xC51 family. It directly controls the microcontroller I/O pins by software without the need of any specific hardware. No other I²C masters are allowed on the bus. Note that the electrical characteristics of this microcontroller family are not conform the I²C specifications.

IIC51M:

IIC51M is a module for multimaster I²C to be used on microcontrollers of the PCB8xC552/C652 family. It makes use of the built-in I²C interface hardware (SIO1) of these microcontrollers. Since this hardware is a multimaster interface other I²C masters are allowed on the bus.

All I²C transfer procedures in IIC51S are fully software interface compatible with IIC51M. This allows a single PLM51 program using I²C to be written for both mentioned microcontroller families.

1.3. Definitions, Acronyms and Abbreviations.

I ² C	Inter-IC bus
PLM51	High level Program Language for 8051 family Microcontrollers
ASM51	Assembly Language for 8051 family Microcontrollers
RL51	Relocating Linker for 8051 family Microcontrollers
S	I ² C Message Start Condition
P	I ² C Message Stop Condition
A	I ² C Message Acknowledge
N	I ² C Message Negative Acknowledge
SivW	I ² C Message Slave Address + Write
SivR	I ² C Message Slave Address + Read
Sub	I ² C Slave Subaddress

NV-Memory I²C Controlled Non Volatile Memory (E²PROM)

PLM51 I²C software interface IIC51 (version 0.5)**ETV/AN89004****1.4. References.**

- | | | |
|-----|---|------|
| [1] | I ² C Specification
I ² C-bus compatible ICs
Philips Components Data Handbook IC12a | 1989 |
| [2] | PL/M-51 User's Guide for DOS Systems
Intel Corporation | 1986 |
| [3] | MSC-51 Macro Assembler User's Guide for DOS Systems
Intel Corporation | 1986 |
| [4] | MSC-51 Utilities User's Guide for DOS Systems
Intel Corporation | 1986 |
| [5] | Single-chip 8-bit microcontrollers PCB83C552/PCB80C552, PCB83C652/PCB80C652 etc.
I ² C-bus compatible ICs
Philips Components Data Handbook IC12a | 1989 |
| [6] | Single-chip 8-bit microcontroller PCB80C51
Integrated circuits Book IC14 | 1987 |

PLM51 I²C software interface IIC51 (version 0.5)

ETV/AN89004

2. GENERAL DESCRIPTION.

2.1. Perspective.

IIC51 is designed for use in stand-alone microcontroller I²C systems. It is mainly written to provide a standard set of procedures for computer controlled television / teletext concepts based on 8051 family microcontrollers.

2.2. Functions.

IIC51 contains the following functions:

- Initialisation of the I²C interface (software and hardware)
- Transfer of I²C messages to and from an I²C slave device
- Error detection
- Automatic retrying if an error occurs during a transfer (up to 5 attempts)
- Error recovery if the bus is held by a slave device that is out of bit-sync
- Optional slave receiver / transmitter function (IIC51M only)

2.3. User Characteristics.

IIC51 is designed to be a easy to use package. All needed code and data is defined in a single object module (IIC51M.OBJ or IIC51S.OBJ). The PLM51 user needs only to link this module to his own application object modules, using Intel's RL51. Procedures and data of concern to the user can be declared EXTERNAL by including the file IIC51.DCL.

2.4. General Constraints.

IIC51 is coded for and translated by the Intel MSC-51 Macro Assembler. It is tested together with Intel PLM51 modules. Intel utilities used for testing:

- MSC-51 Macro Assembler, ASM51.EXE, Version V2.3
- PL/M-51 Compiler, PLM51.EXE, Version V1.2 and V1.3
- MSC-51 Relocator and Linker, RL51.EXE, Version V3.1

Development is done on an IBM-PC/AT running DOS.

IIC51S needs:

- 350 Bytes CODE (approx.)
- 6 Bytes DATA
- 1 Byte Bit-Addressable DATA
- 1 Bit

IIC51M needs:

- 400 Bytes CODE (approx.)
- 6 Bytes DATA
- 1 Byte Bit-Addressable DATA
- 1 Bit
- Exclusive use of Register Bank 1

PLM51 I²C software interface IIC51 (version 0.5)

ETV/AN89004

3. FUNCTIONAL DESCRIPTION.

3.1. Master Mode Functions.

This section describes the available functions in IIC51 on a procedure by procedure bases.

Each procedure must be declared EXTERNAL by the PLM51 user. In this declaration the user can specify the type returned by each procedure. All procedures (except Init_IIC) can return a BIT or a BYTE (depending on the chosen EXTERNAL declaration). The BIT or BYTE returned is 0 if the I²C transmission was successful. If the user decides to declare a procedure untyped, the result of the previous I²C transmission can always be checked by examining the static BIT variable IIC_Error. Note that typed procedures must be called using an expression. If the result of an I²C procedure is to be ignored, a dummy assignment must be done for a typed procedure. An untyped procedure can be called by the PLM51 CALL statement, without any additional overhead. The examples in the follow section assume the procedures to be declared untyped.

Note that the least significant bit of all slaveaddresses passed to the I²C procedures must be 0.

3.1.1. Init_IIC.

Declaration:

```
Init_IIC:
  PROCEDURE ( Own_Slave_Address ) EXTERNAL ;
  DECLARE   ( Own_Slave_Address ) BYTE ;
  END ;
```

Description:

Init_IIC must be called once after reset, before any other procedure is used. It initialises all I²C internal static data and hardware. The Own_Slave_Address is passed to Init_IIC for the optional slave function in a multimaster I²C system (IIC51M). In a singlemaster I²C system (IIC51S), the Own_Slave_Address is ignored. Note that Init_IIC does not effect the global interrupt enable flag (EA). IIC51M requires the user to enable interrupts afterwards (see example).

Example:

```
CALL Init_IIC ( 54h ) ; /* Enable Interrupts; EA = 1 */
ENABLE ;
```

PLM51 I²C software interface IIC51 (version 0.5)

ETV/AN89004

3.1.2. IIC_Test_Device.

Declaration:

```

IIC_Test_Device:
  PROCEDURE ( Slave_Address ) [ BIT | BYTE ] EXTERNAL ;
  DECLARE   ( Slave_Address ) BYTE ;
  END ;

```

Description:

IIC_Test_Device just sends the slaveaddress on the I²C bus. It can be used to check the presence of a device on the I²C bus.

I²C Protocol:

S	SlvW	A	P
---	------	---	---

 (Device is Present, IIC_Error = 0)

OR

S	SlvW	N	P
---	------	---	---

 (Device is Not Present, IIC_Error = 1)
Example:

```

DECLARE IIC_Error BIT EXTERNAL ;
.....
CALL IIC_Test_Device ( 8Ch ) ;
IF ( IIC_Error ) THEN
  "Device is Not Present Handling"
ELSE
  "Device is Present Handling"

```

PLM51 I²C software interface IIC51 (version 0.5)

ETV/AN89004

3.1.3. IIC_Write.

Declaration:

```

IIC_Write:
  PROCEDURE ( Slave_Address, Count, Source_Ptr ) [ BIT | BYTE ] EXTERNAL ;
  DECLARE   ( Slave_Address, Count, Source_Ptr ) BYTE ;
  END ;

```

Description:

IIC_Write is the most basic procedure to write a message to a slave device.

I²C Protocol:

L = Count
D1[0..L-1] BASED by Source_Ptr

S	SlvW	A	D1[0]	A	D1[1]	A	...	A	D1[L-1]	A	P
---	------	---	-------	---	-------	---	-----	---	---------	---	---

Example:

```

DECLARE Data_Buffer ( 4 ) BYTE ;
.....
CALL IIC_Write ( 0C2h, LENGTH ( Data_Buffer ), .Data_Buffer ) ;

```

PLM51 I²C software interface IIC51 (version 0.5)

ETV/AN89004

3.1.4. IIC_Write_Sub.

Declaration:

```

IIC_Write_Sub:
  PROCEDURE ( Slave_Address, Count, Source_Ptr, Sub_Address )
    [ BIT | BYTE ] EXTERNAL ;
  DECLARE ( Slave_Address, Count, Source_Ptr, Sub_Address ) BYTE ;
  END ;

```

Description:


IIC_Write_Sub writes a message preceded by a subaddress to a slave device.

I²C Protocol:

```

L      = Count
Sub    = Sub_Address
D1[0..L-1] BASED by Source_Ptr

```

Example:

```

DECLARE Data_Buffer ( 8 ) BYTE ;
.....
CALL IIC_Write_Sub ( 48h, LENGTH ( Data_Buffer ), .Data_Buffer, 2 ) ;

```

PLM51 I²C software interface IIC51 (version 0.5)

ETV/AN89004

3.1.5. IIC_Write_Sub_SWInc.

Declaration:

```

IIC_Write_Sub_SWInc:
  PROCEDURE ( Slave_Address, Count, Source_Ptr, Sub_Address )
    [ BIT | BYTE ] EXTERNAL ;
  DECLARE ( Slave_Address, Count, Source_Ptr, Sub_Address ) BYTE ;
  END ;

```

Description:




Some I²C devices addressed with a subaddress do not automatically increment the subaddress after reception of each byte. IIC_Write_Sub_SWInc can be used for such devices the same way IIC_Write_Sub is used. IIC_Write_Sub_SWInc splits up the message in smaller messages and increments the subaddress itself.

I²C Protocol:

```

L      = Count
Sub    = Sub_Address
D1[0..L-1] BASED by Source_Ptr

```

Example:

```

DECLARE Data_Buffer ( 6 ) BYTE ;
.....
CALL IIC_Write_Sub_SWInc ( 80h, LENGTH ( Data_Buffer ), .Data_Buffer, 0 ) ;

```


PLM51 I²C software interface IIC51 (version 0.5)

ETV/AN89004

3.1.6. IIC_Write_Memory.

Declaration:

```

IIC_Write_Memory:
PROCEDURE ( Slave_Address, Count, Source_Ptr, Sub_Address )
      [ BIT | BYTE ] EXTERNAL ;
DECLARE   ( Slave_Address, Count, Source_Ptr, Sub_Address ) BYTE ;
END ;

```

Description:


I²C Non-Volatile Memory devices (such as PCF8582) need an additional delay after writing a byte to it. IIC_Write_Memory can be used to write to such devices the same way IIC_Write_Sub is used. IIC_Write_Memory splits up the message in smaller messages and increments the subaddress itself. After transmission of each small message a delay of 40 milliseconds is inserted.

I²C Protocol:

```

L      = Count
Sub    = Sub_Address
D1[0..L-1] BASED by Source_Ptr

```

Example:

```

DECLARE Data_Buffer ( 10 ) BYTE ;
.....
CALL IIC_Memory ( 0A0h, LENGTH ( Data_Buffer ), .Data_Buffer, 0F0h ) ;

```

PLM51 I²C software interface IIC51 (version 0.5)

ETV/AN89004

3.1.7. IIC_Write_Sub_Write.

Declaration:

```

IIC_Write_Sub_Write:
PROCEDURE ( Slave_Address, Count1, Source_Ptr1, Sub_Address, Count2, Source_Ptr2 )
      [ BIT | BYTE ] EXTERNAL ;
DECLARE   ( Slave_Address, Count1, Source_Ptr1, Sub_Address, Count2, Source_Ptr2 )
      BYTE ;
END ;

```

Description:


IIC_Write_Sub_Write writes 2 data blocks preceded by a subaddress in one message to a slave device. This procedure can be used for devices that need an extended addressing method, without the need to put all data into one large buffer. Such a device is the ECCT (I²C controlled teletext device; see example).

I²C Protocol:

```

L      = Count1
M      = Count2
Sub    = Sub_Address
D1[0..L-1] BASED by Source_Ptr1
D2[0..M-1] BASED by Source_Ptr2

```

Example:

```

PROCEDURE Write_CCT_Memory ( Chapter, Row, Column, Data_Buf, Data_Count ) ;
DECLARE ( Chapter, Row, Column, Data_Buf, Data_Count ) BYTE ;

```

The extended address (CCT-Cursor) is formed by Chapter, Row and Column. These three bytes are written after the subaddress (8) followed by the actual data which will be stored relative to the extended address.

```

CALL IIC_Write_Sub_Write ( 22h, 3, .Chapter, 8, Data_Buf, Data_Count ) ;

```

```

END Write_CCT_Memory ;

```

PLM51 I²C software interface IIC51 (version 0.5)

ETV/AN89004

3.1.8. IIC_Read.

Declaration:

```

IIC_Read:
  PROCEDURE ( Slave_Address, Count, Dest_Ptr ) [ BIT | BYTE ] EXTERNAL ;
  DECLARE   ( Slave_Address, Count, Dest_Ptr ) BYTE ;
  END ;


```

Description:

IIC_Read is the most basic procedure to read a message from a slave device.

I²C Protocol:

M = Count
D2[0..M-1] BASED by Dest_Ptr

Example:

```

DECLARE Data_Buffer ( 4 ) BYTE ;
.....
CALL IIC_Read ( 0B4h, LENGTH ( Data_Buffer ), .Data_Buffer ) ;

```

PLM51 I²C software interface IIC51 (version 0.5)

ETV/AN89004

3.1.9. IIC_Read_Status.

Declaration:

```

IIC_Read_Status:
  PROCEDURE ( Slave_Address, Dest_Ptr ) [ BIT | BYTE ] EXTERNAL ;
  DECLARE   ( Slave_Address, Dest_Ptr ) BYTE ;
  END ;


```

Description:

A lot of I²C devices have only a one status byte that can be read via I²C. IIC_Read_Status can be used for this purpose. IIC_Read_Status works the same as IIC_Read but the user does not have to pass a count parameter.

I²C Protocol:

M = Count
Status BASED by Dest_Ptr

Example:

```

DECLARE Status_Byte BYTE ;
.....
CALL IIC_Read_Status ( 84h, .Status_Byte ) ;

```

PLM51 I²C software interface IIC51 (version 0.5)

ETV/AN89004

3.1.10. IIC_Read_Sub.

Declaration:

```

IIC_Read_Sub:
  PROCEDURE ( Slave_Address, Count, Dest_Ptr, Sub_Address )
    [ BIT | BYTE ] EXTERNAL ;
  DECLARE ( Slave_Address, Count, Dest_Ptr, Sub_Address ) BYTE ;
  END ;

```

Description:


IIC_Read_Sub reads a message from a slave device preceded by a write of the subaddress. Between writing the subaddress and reading the message an I²C restart condition is generated without surrendering the bus. This prevents other masters from accessing the slave device in between and overwriting the subaddress.

I²C Protocol:

```

M      = Count
Sub    = Sub_Address
D2[0..M-1] BASED by Dest_Ptr

```

Example:

```

DECLARE Data_Buffer ( 5 ) BYTE ;
.....
CALL IIC_Write_Sub ( 0A2h, LENGTH ( Data_Buffer ), .Data_Buffer, 2 ) ;

```

PLM51 I²C software interface IIC51 (version 0.5)

ETV/AN89004

3.1.11. IIC_Write_Sub_Read.

Declaration:

```

IIC_Write_Sub_Read:
  PROCEDURE ( Slave_Address, Count1, Source_Ptr1, Sub_Address, Count2, Dest_Ptr2 )
    [ BIT | BYTE ] EXTERNAL ;
  DECLARE ( Slave_Address, Count1, Source_Ptr1, Sub_Address, Count2, Dest_Ptr2 )
    BYTE ;
  END ;

```

Description:


IIC_Write_Sub_Read writes a data block preceded by a subaddress, generates an I²C restart condition, and reads a data block. This procedure can be used for devices that need an extended addressing method. Such a device is the ECCT (I²C controlled teletext device; see example).

I²C Protocol:

```

L      = Count1
M      = Count2
Sub    = Sub_Address
D1[0..L-1] BASED by Source_Ptr1
D2[0..M-1] BASED by Dest_Ptr2

```

Example:

```

PROCEDURE Read_CCT_Memory ( Chapter, Row, Column, Data_Buf, Data_Count ) ;
DECLARE ( Chapter, Row, Column, Data_Buf, Data_Count ) BYTE ;

```

```

/*
  The extended address (CCT-Cursor) is formed by Chapter, Row and Column. These
  three bytes are written after the subaddress (8). After that the actual data will be
  read relative to the extended address.
*/

```

```

CALL IIC_Write_Sub_Read ( 22h, 3, .Chapter, 8, Data_Buf, Data_Count ) ;

```

```

END Read_CCT_Memory ;

```

PLM51 I²C software interface IIC51 (version 0.5)

ETV/AN89004

3.2. Slave Mode Functions.

I²C slave mode is provided by IIC51M only. All slave mode actions (except initialisation) take place in the SIO1 interrupt procedure. Slave mode I²C protocol is very application dependent. If a specific slave mode is required, the user has to modify three procedures in IIC51M at source level. The following sections describe these procedures. The program examples of the procedures implement an I²C slave protocol to read and write the microcontroller's on chip RAM via I²C. This can be a useful feature during program development and debugging.

3.2.1. Init_Slave.

This procedure is called from IIC_Init. In this procedure the user can initialise all static data concerning slave mode functions (if any).

Example:

```
Slave_Sub_Address: db 1
.....
Init_Slave:      mov Slave_Sub_Address,#0 ; Initialise Sub Address
                  ret
```

3.2.2. Receive_Slave.

Receive_Slave is a procedure called from the SIO1 interrupt procedure each time a byte is received from another I²C master. The procedure can make use of the bit "IICNtrl.BYTE1EXPECTED", as defined in IIC51M. This bit is set to logic 1, every time the first data byte of an I²C message is about to be received. Receive_Slave can use this bit to detect the start of a new message.

Normally all bytes received from the other master will be acknowledged (i.e. SIO1 control bit Assert Acknowledge is set, AA = 1). If AA is cleared by Receive_Slave subsequent bytes in the message will be ignored and a negative acknowledge will be transmitted after reception of each byte. Note that the example does not make use of this feature.

Constraints:

- Receive_Slave must read the S1DAT register.
- Receive_Slave may clear the SIO1 control bit AA, to stop acknowledging data.
- Receive_Slave may not effect any other SIO1 hardware registers / bits.
- Receive_Slave is only allowed to use the accumulator and register R0 in the current registerbank.

Example:

```
Receive_Slave:  mov a,S1DAT                ; Pick up data
                  mov r0,#Slave_Sub_Address ; Prepare for 1st byte
                  jbc IICNtrl.BYTE1EXPECTED,Save_Byte ; Jump if 1st byte
                  mov r0,Slave_Sub_Address ; Else data byte
                  inc Slave_Sub_Address      ; Postincrement Sub.
Save_Byte:      mov @r0,a                  ; Save Data
                  ret                       ; Exit
```

PLM51 I²C software interface IIC51 (version 0.5)

ETV/AN89004

3.2.3. Send_Slave.

Send_Slave is a procedure called during the SIO1 interrupt procedure each time a byte has to be transmitted to another I²C master. This occurs after reception of I²C startcondition followed by the microcontroller's own slaveaddress (as passed to Init_IIC) with read-bit. Send_Slave will be called again after transmission of each subsequent byte, until a negative acknowledge is received from the reading I²C master.

Constraints:

- Send_Slave must write to the S1DAT register.
- Send_Slave may not effect any other SIO1 hardware registers / bits.
- Send_Slave is only allowed to use the accumulator and register R0 in the current registerbank.

Example:

```
Send_Slave:      mov r0,Slave_Sub_Address ; Pick up Sub Address
                  mov S1DAT,@r0           ; Send Data
                  inc Slave_Sub_Address    ; Postincrement Sub.
                  ret                       ; Exit
```